


pull handles

Fixing Information

All Alpro handles are supplied with their own dedicated fixing packs, which suit all the possible door materials available. Full fixing and maintenance instructions are included in the handle kits, to ensure the correct methodology is employed when fixing the handles. In the event of the fixing kits being mislaid or broken, replacement kits are available by contacting the Alpro sales office on 01202 676262 and specifying the necessary requirements. The handles can be used on all types of doors.




F17

39-54mm thick doors

For 32mm Ø Impressionist handles

For 25, 32 & 38mm Ø Functional 98 series handles

M12-70mm countersunk



F18


55-85mm thick doors

or 32mm Ø Impressionist handles

For 25, 32 & 38mm Ø Functional 98 series handles

M12-90mm countersunk

For black cover cap - F18BLACK




F19

39-54mm thick doors

or 32mm Ø Impressionist handles

For 25, 32 & 38mm Ø Functional 98 series handles

M12-90mm with M6 grub screw




F20

55-85mm thick doors

or 32mm Ø Impressionist handles

For 25, 32 & 38mm Ø Functional 98 series handles

M12-120mm with M6 grub screw



F21

Glass doors


For 32mm Ø Impressionist handles

For 25, 32 & 38mm Ø Functional 98 series handles

M12-55.5mm with M6 grub screw


pull handles

Fixing Information




F22 Secret fixing

For fixing to a wooden door 25mm deep
For Impressionist and Functional 98 Handles
NB - Use these fixings for timber doors only
(This fixing is not recommended on Aluminium doors)




F25.2KIT

Glass doors (Single side)
For Impressionist handles
For Functional 98 series - single side glass
fixing 2 x 90mm XM12 bolts
Snake eye fixing 25mm head x 5mm thick




F26

39-54mm thick doors
For 32mm Ø Impressionist handles
For 25, 32 & 38mm Ø Functional 98 series
handles
M12-70mm countersunk with dome cap
NB - Cover cap is available in black on
request



F27

10mm Ø clearance hole required
For Functional 97 Series handles
*Suitable for back to back pairs and single
handles




F28

10mm Ø clearance hole required
For Functional 97 Series handles
*Suitable for back to back pairs and single
handles

pull handles

Fixing Information




F29

Minimum 11.5mm Ø clearance hole required, maximum 12mm

For Functional 97 Series handles

*Suitable for back to back pairs and single handles




F34

M12 fixings

For 32mm Ø Impressionist handles

For 25, 32 & 38mm Ø Functional 98 series handles


M12 x 25mm long hexagon headed bolt grade 8.8.



F38

For Functional 97 Series handles only

M6 x 20mm long countersunk bolt and 4 off No. 8 x 25 long wood screws



HOLE SIZES FOR FIXING THROUGH:

For M12 fixing - Wood & Aluminium = 13mm Ø

For M12 fixing - Glass = 18mm Ø